INTAKE MANIFOLD PRESSURE CONTROL
FOR VARIABLE DISPLACEMENT ENGINES

BACKGROUND OF THE INVENTION

1.   Field of the Invention

The present invention relates to a system and method for controlling a variable displacement engine.

2.   Background Art

Fuel economy for a multi-cylinder internal combustion engine can be improved by deactivating some of the engine cylinders under certain operating conditions. Reducing the number of operating cylinders reduces the effective displacement of the engine such that it is sometimes referred to as a variable displacement engine. Depending upon the particular configuration of the variable displacement engine, one or more cylinders may be selectively deactivated to improve fuel economy under light load conditions, for example. In some engine configurations, a group of cylinders, which may be an entire bank of cylinders, is selectively deactivated.

Some variable displacement engines include separate intake manifolds and plenums for each bank of cylinders. When a bank of cylinders is deactivated, the intake manifold pressure approaches the current ambient barometric pressure. When reactivated, the bank of cylinders will produce near maximum torque until the associated manifold pressure is pulled down to a steady state vacuum.

- 1 -

SUMMARY OF THE INVENTION

The present invention pre-positions engine actuators based on engine operating conditions to reduce torque excursions during reactivation of a group or bank of cylinders.

Embodiments of the present invention include a system and method for controlling a variable displacement engine to deliver a desired torque that determine current engine operating conditions and pre-position one or more airflow actuators associated with one or more deactivated cylinders to provide the desired torque assuming those cylinders were activated. In one embodiment, the engine control strategy determines the cylinder air charge to achieve a desired torque based on engine speed, intake manifold pressure, and number of currently activated cylinders. A variable cam timing phase or angle associated with a deactivated cylinder bank is then pre-positioned based on the engine speed, intake manifold pressure, desired torque and number of cylinders to be reactivated.

The present invention provides a number of advantages. For example, the present invention uses pre-position control to reduce the time required to properly position airflow actuators when reactivating cylinders resulting in reduced torque variation or excursions from desired torque.

The above advantage and other advantages, objects, and features of the present invention will be readily apparent from the following detailed description of the preferred embodiments when taken in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a block diagram illustrating operation of one embodiment for a system or method for controlling a variable displacement engine according to the present invention;

Figure 2 is a block diagram illustrating one embodiment of a variable cam timing mechanism which may be pre-positioned according to the present invention;

Figure 3 is a block diagram illustrating operation of one embodiment for a system or method for pre-positioning airflow actuators according to the present invention; and

Figure 4 provides a graphical representation of the relationship between variable cam timing phase angle, air charge, and MAP according to one embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

A block diagram illustrating an engine control system for a representative internal combustion engine operable in a variable displacement mode according to the present invention is shown in Figure 1. System 10 preferably includes an internal combustion engine 12 having a plurality of cylinders, represented by cylinder 14. In one preferred embodiment, engine 12 includes ten cylinders arranged in a "V" configuration having two cylinder banks 16, 18 with five cylinders each. As used herein, a cylinder bank refers to a related group of cylinders having one or more common characteristics, such as being located proximate one another or having a common emission control device (ECD), intake manifold, and/or exhaust manifold for example. This would include configurations having a group of

- 3 -

cylinders on the same side of the engine treated as a bank even though these cylinders may not share a common intake or exhaust manifold, i.e., the exhaust manifold could be configured with separate exhaust runners or branches if desired or beneficial. Likewise, cylinder banks can also be defined for in-line cylinder configurations which are within the scope of the present invention.

As one of ordinary skill in the art will appreciate, system 10 includes various sensors and actuators to effect control of the engine. One or more sensors or actuators may be provided for each cylinder 14, or a single sensor or actuator may be provided for the engine. For example, each cylinder 14 may include four actuators which operate corresponding intake and exhaust valves, while only including a single engine coolant temperature sensor for the entire engine. However, the block diagrams of the Figures generally illustrate only a single type of sensor for ease of illustration and description.

System 10 preferably includes a controller 20 having a microprocessor 22 in communication with various computer-readable storage media, indicated generally by reference numeral 24. The computer readable storage media preferably include a read-only memory (ROM) 26, a random-access memory (RAM) 28, and a keep-alive memory (KAM) 30. As known by those of ordinary skill in the art, KAM 30 is used to store various operating variables while controller 20 is powered down but is connected to the vehicle battery. Computer-readable storage media 24 may be implemented using any of a number of known memory devices such as PROMs, EPROMs, EEPROMs, flash memory, or any other electric, magnetic, optical, or combination memory device capable of storing data, some of which represent executable instructions, used by microprocessor 22 in controlling the

engine. Microprocessor 22 communicates with the various
sensors and actuators via an input/output (I/O) interface
32. Of course, the present invention could utilize more
than one physical controller, such as controller 20, to
5   provide engine/vehicle control depending upon the particular
application.

In the embodiment illustrated in Figure 1, each
bank of cylinders 16, 18 includes an associated dedicated
intake manifold 36, 38 and plenum 40, 42. Each cylinder bank
10   16, 18 preferably includes associated airflow actuators
which may include one or more throttle valves 44, 46 and/or
intake/exhaust valves for each cylinder 14. The
intake/exhaust valves may be actuated using a variable cam
timing (VCT) or phasing mechanism as illustrated and
15   described with reference to Figure 2, for example.
Alternatively, electromagnetic valve actuators may be used
to provide variable valve timing (VVT) for throttle-less
applications, for example. Those of ordinary skill in the
art will recognize various other airflow actuators that may
20   be used to control the manifold or cylinder pressure during
reactivation of a deactivated cylinder or bank of cylinders
according to the present invention.

System 10 preferably includes a mass airflow
sensor 48, 50 associated with each intake 36, 38 which
25   provide corresponding signals (MAF_A, MAF_B) to controller 20
indicative of the mass airflow. If one or both mass airflow
sensors is omitted, corresponding mass airflow value(s) may
be inferred from various engine operating parameters.
Throttle valves 44, 46, which are preferably electronically
30   controlled throttle valves, may be used to modulate the
airflow and corresponding intake manifold pressure through
intakes 36, 38 during certain operating modes. Throttle
valves 44, 46 may be controlled in tandem or independently

depending upon the particular application. Alternatively, the present invention may be used in throttle-less applications which may use electronically controlled valves and variable valve timing to modulate intake airflow as described above. Throttle valves 44, 46 are preferably electronically controlled by appropriate actuators 52, 54 based on a corresponding throttle position signal generated by controller 20 with a throttle position sensor providing a feedback signal indicative of the actual position to implement closed loop control.

As illustrated in Figure 1, manifold absolute pressure sensors 56, 58 may be used to provide a signal (MAP) indicative of the manifold pressures to controller 20. Air passing through intakes 36, 38 enters the combustion chambers or cylinders 14 through appropriate control of one or more intake valves. The intake and exhaust valves may be controlled directly or indirectly by controller 20 along with ignition timing (spark) and fuel to selectively activate/deactivate one or more cylinders 14 to provide variable displacement operation. According to the present invention, one or more airflow actuators associated with a deactivated bank of cylinders are controlled or pre-positioned to reduce or eliminate torque excursions associated with reactivation. In one embodiment, the airflow actuators include a dedicated throttle valve and variable cam timing (VCT) mechanism associated with the deactivated bank of cylinders.

A fuel injector 60 injects an appropriate quantity of fuel in one or more injection events for the current operating mode based on a signal generated by controller 20 processed by an appropriate driver. Control of the fuel injection events is generally based on the position of the pistons within respective cylinders 14. Position

- 6 -

information is acquired by an appropriate crankshaft sensor which provides a position signal indicative of crankshaft rotational position. At the appropriate time during the combustion cycle, controller 20 generates a spark signal that is processed by ignition system 62 to control spark plug 64 and initiate combustion within an associated cylinder 14.

Controller 20 (or a camshaft arrangement) controls one or more exhaust valves to exhaust the combusted air/fuel mixture of activated or running cylinders through an associated exhaust manifold, indicated generally by reference numerals 66, 68. Depending upon the particular engine configuration, one or more exhaust manifolds may be used. In one preferred embodiment, engine 12 includes an exhaust manifold 66, 68 associated with each bank of cylinders as illustrated in Figure 1.

Exhaust gas oxygen sensors 70, 72 are preferably associated with each bank of cylinders and provide a signal indicative of the oxygen content of the exhaust gases to controller 20. As known by those of ordinary skill in the art, the EGO signal may be used as feedback in a closed loop controller to control the air/fuel ratio provided to the one or more cylinders. In one embodiment, heated exhaust gas oxygen sensors (HEGO) are used. The exhaust gas oxygen sensor signals may be used to independently adjust the air/fuel ratio, or control the operating mode of one or more cylinders or banks of cylinders. During operation, the exhaust gas passes through the exhaust manifolds 66, 68 to associated emission control devices (ECDs) 74-80, before exiting the tailpipes 82, 84. While illustrated in a "straight pipe" configuration with each bank having associated ECDs and exhaust tailpipes, the present invention

is equally applicable to "Y-pipe" configurations, which combine the exhaust from both banks of cylinders.

Additional sensors/actuators, represented generally by reference numeral 90, may also interface with controller 20 as described in greater detail with reference to Figure 2.

According to the present invention, controller 20 controls one or more dedicated airflow actuators such as throttle valves 44, 46 and/or variable cam timing mechanisms 200 (Fig. 2) associated with a deactivated bank of cylinders based on current operating conditions associated with the activated cylinders to reduce torque excursions during reactivation. In a preferred embodiment, engine 12 is a V-10 engine with variable displacement operation provided by selectively deactivating one bank of cylinders under appropriate engine and/or vehicle operating conditions, such as light load, for example. The variable cam timing mechanism is pre-positioned based on engine speed and intake manifold pressure of the activated bank of cylinders to be ready for the transition to reactivation faster than scheduling the cam position when a transition is actually desired. The engine speed and intake manifold pressure of the activated bank of cylinders are preferably determined using corresponding sensors. Of course, those of ordinary skill in the art will appreciate that these values may also be calculated or estimated based on one or more other sensors. The present invention determines the cylinder air charge needed on the deactivated bank of cylinders as if the engine were currently running in full cylinder mode, preferably using a lookup table. The invention then calculates the required airflow actuator position(s) to achieve the required cylinder air charge and commands the cam timing mechanism, throttle valve, and/or valve

- 8 -

positioning to achieve the required cylinder air charge. When a transition from partial to full cylinder operation is desired, the airflow actuator(s) will be in the desired starting position such that undesirable torque excursions are reduced or eliminated.

Figure 2 is a block diagram illustrating a variable cam timing mechanism that may be used for pre-positioning according to the present invention. As illustrated in Figure 2, the present invention may be used in a direct injection engine or a more conventional port injected engine (not shown). For ease of description and illustration of the representative variable cam timing mechanism, only a single cylinder is illustrated. Of course, for a variable displacement engine having dedicated airflow actuators according to the present invention, independent or integrated variable cam timing mechanisms may be used to independently control the various groups or banks of cylinders that provide variable displacement operation.

The illustrated direct injection spark ignited internal combustion engine includes a plurality of combustion chambers 130 having combustion chamber walls 132 with piston 136 positioned therein and connected to crankshaft 140. Combustion chamber, or cylinder, 130 is shown communicating with intake manifold 36 and exhaust manifold 66 via respective intake valves 152a and 152b (not shown), and exhaust valves 154a and 154b (not shown). Fuel injector 60 is shown directly coupled to combustion chamber 130 for delivering liquid fuel directly therein in proportion to the pulse width of signal fpw received from engine controller 20 (Fig. 1) via a conventional electronic driver. Fuel is delivered to fuel injector 60 by a conventional high-pressure fuel system (not shown) including a fuel tank, fuel pumps, and a fuel rail.

Engine 12 also may determine current operating
conditions via signals generated by corresponding sensors,
such as an engine coolant temperature sensor 212 coupled to
cooling sleeve 214, and a profile ignition pickup signal
5   (PIP) from Hall effect sensor 218 coupled to crankshaft 140.
Engine speed signal RPM is generated by controller 20 from
signal PIP in a conventional manner. In a preferred aspect
of the present invention, sensor 218, which is also used as
an engine speed sensor, produces a predetermined number of
10   equally spaced pulses every revolution of the crankshaft.
Continuing with Figure 2, a representative
variable cam timing (VCT) mechanism, indicated generally by
reference numeral 200, is shown. VCT mechanism 200
cooperates with camshaft 230, which is shown communicating
15   with rocker arms 232 and 234 for variably actuating intake
valves 152a, 152b and exhaust valves 154a, 154b. Camshaft
230 is directly coupled to housing 236. Housing 236 forms a
toothed wheel having a plurality of teeth 238. Housing 236
is hydraulically coupled to an inner shaft (not shown),
20   which is in turn directly linked to camshaft 230 via a
timing chain (not shown). Therefore, housing 236 and
camshaft 230 rotate at a speed substantially equivalent to
the inner camshaft. The inner camshaft rotates at a
constant speed ratio to crankshaft 140. However, by
25   manipulation of the hydraulic coupling as described herein,
the relative position of camshaft 230 to crankshaft 140 can
be varied by hydraulic pressures in advance chamber 242 and
retard chamber 244. By allowing high-pressure hydraulic
fluid to enter advance chamber 242, the relative
30   relationship between camshaft 230 and crankshaft 140 is
advanced. Thus, intake valves 152a, 152b and exhaust valves
154a, 154b open and close at a time earlier than normal
relative to crankshaft 140. Similarly, by allowing high-

pressure hydraulic fluid to enter retard chamber 244, the
relative relationship between camshaft 230 and crankshaft
140 is retarded. Thus, intake valves 152a, 152b and exhaust
valves 154a, 154b open and close at a time later than normal
5   relative to crankshaft 140.

Teeth 238, being coupled to housing 236 and
camshaft 230, allow for measurement of relative cam position
via cam timing sensor 250, which provides signal VCT to
controller 20 (Fig. 1). Teeth 1, 2, 3, and 4 are preferably
10   used for measurement of cam timing and are equally spaced
(for example, in a V-8 dual bank engine, spaced 90E apart
from one another), while tooth 5 is preferably used for
cylinder identification. In addition, controller 20 (Fig.
1) sends control signals (LACT, RACT) to conventional
15   solenoid valves (not shown) to control the flow of hydraulic
fluid either into advance chamber 242, retard chamber 244,
or neither.

Relative cam timing is measured, in general terms,
using the time, or rotation angle between the rising edge of
20   the PIP signal and receiving a signal from one of the
plurality of teeth 238 on housing 236 to provide a measure
of the relative cam timing. For the particular example of a
V-8 engine, with two cylinder banks and a five-toothed
wheel, a measure of cam timing for a particular bank is
25   received four times per revolution, with the extra signal
used for cylinder identification.

The diagram of Figure 3 generally represents
control logic for one embodiment of a system or method
according to the present invention. As will be appreciated
30   by one of ordinary skill in the art, the diagram may
represent any one or more of a number of known processing
strategies such as event-driven, interrupt-driven, multi-
tasking, multi-threading, and the like. As such, various

steps or functions illustrated may be performed in the
sequence illustrated, in parallel, or in some cases omitted.
Likewise, the order of processing is not necessarily
required to achieve the objects, features, and advantages of
5   the invention, but is provided for ease of illustration and
description. Although not explicitly illustrated, one of
ordinary skill in the art will recognize that one or more of
the illustrated steps or functions may be repeatedly
performed depending upon the particular processing strategy
10   being used.

Preferably, the control logic is implemented
primarily in software executed by a microprocessor-based
engine controller. Of course, the control logic may be
implemented in software, hardware, or a combination of
15   software and hardware depending upon the particular
application. When implemented in software, the control
logic is preferably provided in a computer-readable storage
medium having stored data representing instructions executed
by a computer to control the engine. The computer-readable
20   storage medium or media may be any of a number of known
physical devices which utilize electric, magnetic, and/or
optical devices to temporarily or persistently store
executable instructions and associated calibration
information, operating variables, and the like.

25   A flow diagram illustrating operation of one
embodiment for a system or method for controlling dedicated
airflow actuators associated with a deactivated bank of
cylinders of a variable displacement engine according to the
present invention is shown in Figure 3. A desired torque is
30   determined as represented by block 300. The desired torque
may be determined based on current ambient and/or engine
operating parameters, such as accelerator pedal position,
barometric pressure, engine speed and/or vehicle speed, for

example. During operation in the variable displacement
mode, a subset of cylinders, preferably an entire bank, is
deactivated and does not contribute to the output torque.
As such, the desired torque must be delivered by the
currently activated cylinders via appropriate control of the
actuators, including the throttle valve, variable cam timing
mechanism, ignition, and fueling, for example.

In one embodiment, a current air charge is
determined to deliver the desired torque using the activated
cylinders based on the engine speed and manifold pressure
associated with the activated cylinders as represented by
blocks 302 and 304, respectively. The engine speed and
manifold pressure may be determined by corresponding sensors
or estimated, as described above. The current engine
operating point (typically determined based on engine speed
and load) can then be used to access a lookup table or
calculation to determine the desired manifold pressure
associated with the deactivated cylinders and associated
actuator positioning as if the engine were using all
cylinders, i.e., as if the deactivated cylinders were
reactivated, with the actuators being pre-positioned in
anticipation of reactivation.

A desired manifold pressure associated with the
deactivated cylinders is determined as represented by block
306. The desired manifold pressure may be determined using
one or more lookup tables, functions and/or calculations
alone or in combination based on the engine operating point
or its components (engine speed and load), for example. A
corresponding desired air charge for the deactivated
cylinders is then determined using the engine speed and the
desired manifold pressure for the deactivated cylinders upon
reactivation as represented by block 308. One or more
actuators associated with the deactivated cylinders are then

controlled or pre-positioned based on the operating
conditions of the activated cylinders as represented by
block 310, and illustrated in Figure 4. The actuators may
include a variable cam timing mechanism as represented by

5   block 312, for which a representative embodiment 110 was
illustrated and described with reference to Figure 2. The
actuators may also include a throttle valve as represented
by block 314, such as the electronically controlled throttle
valves 44, 46 illustrated and described with reference to

10   Figure 1, for example. In one embodiment, a third-order
polynomial expression of air charge is used to determine a
desired cam angle with the coefficients of the polynomial
stored in a plurality of lookup tables indexed by manifold
pressure (MAP) and engine speed. The air charge values are

15   determined from the airflow per cylinder that would be
required to produce the current desired torque if the engine
was operating on all cylinders. A representative polynomial
expression is given by:

20   Cam_angle = C_0 + C_1 * air_charge + C_2 * air_charge^2 + C_3
     * air_charge^3

where the coefficients C_0, C_1, C_2, and C_3 are stored in lookup
tables indexed by engine speed and MAP.

25   Figure 4 provides a graphical representation of
the relationship between variable cam timing phase angle,
air charge, and MAP according to one embodiment of the
present invention. As illustrated in Figure 4, a family of
curves 400 representing lines of constant MAP (from about 6

30   in. Hg to about 28 in. Hg) illustrate the relationship
between air charge 402 (determined using current engine
speed) and an engine actuator, with the actuator position
generally represented by VCT phase angle 404. Of course,

other actuators may also be pre-positioned according to the present invention, such as a dedicated throttle valve, for example. Alternatively, the engine speed and intake manifold pressure of the activated cylinders may be used to determine the cylinder air charge needed on the deactivated bank of cylinders using a calculation alone or in combination with one or more lookup tables. The cylinder air charge needed for the deactivated bank of cylinders may then be used to determine the appropriate actuator position using a lookup table indexed by air charge and MAP as illustrated in Figure 4, for example. The actuator(s) associated with the deactivated cylinders is(are) then pre-positioned to improve response and reduce torque excursions during reactivation. For air charge values that do not intersect a particular MAP curve, a corresponding maximum (or minimum) value for the actuator position may be used. This value may be further adjusted or limited to assure stable combustion with any additional torque adjustments necessary to provide the desired torque provided by spark and/or fuel control. For example, a MAP value of 28 in. Hg has a maximum VCT phase angle of about 50 degrees, which corresponds to an air charge value of about 5. As such, for any air charge values of less than 5, a maximum VCT phase angle of about 50 degrees is used. This value may be adjusted based on the current operating conditions to assure stable combustion. Additional torque adjustments are then provided by fuel and/or spark control as necessary to provide the current desired torque.

As such, in the embodiment of the present invention described above, the electronic engine control strategy determines the cylinder air charge needed for the deactivated bank of cylinders as if the engine were currently running in full cylinder mode. The control

- 15 -

strategy then calculates the required variable cam timing based on engine speed and desired manifold pressure to achieve the required cylinder air charge. The controller then commands the cam to the corresponding position. The control system continues to evaluate and command the cam position based on current engine operation conditions. In the event of a transition from partial to full cylinder operation is desired, the camshaft will be in the proper starting position. As such output torque variation is reduced to provide better driveability during reactivation.

By proper pre-positioning of variable cam timing associated with a deactivated bank of cylinders, the present invention reduces the time required to pull down the associated intake manifold pressure from ambient barometric pressure such that any excess torque is reduced or eliminated and driveability is improved.

While the best mode for carrying out the invention has been described in detail, those familiar with the art to which this invention relates will recognize various alternative designs and embodiments for practicing the invention as defined by the following claims.